







Dekoder Vergleichstabelle

Dekoder	Prottime Elite Pro Decoder	Prottime Elite Decoder	Prottime Decoder	Distant Decoder	Charger Case	Transponder Tester
Characteristika:						
Auflösung	0,0001 s	0,001 s	0,001 s	0,001 s	Aluminum Koffer	
Präzision	0,2 ppm	0,5 ppm	0,5 ppm	0,5 ppm	Kapazität: 40 Transponders	
kompatible Transponder	All	All	All	All	Alle ausser RK and RCS	Alle ausser RK and RCS
Loops	2	2	1	1		ziegt Transponde Nummer und Akku-status
Streckenbreite	Passive Loop: max. 25m Active Loop: max. 25m	Passive Loop: max. 25m Active Loop: max. 25m	Passive Loop: max. 25m Active Loop: max. 25m	Passive Loop: max. 25m Active Loop: max. 25m		
Loop-Dekoder Entfernung	max. 100m coaxial cable	max. 100m coaxial cable	max. 100m coaxial cable	max. 100m coaxial cable		
Interner Speicher	2000 passings	2000 passings	2000 passings	2000 passings		
GPS Synchronisation	Yes	Yes	No	Option	Ladezeit: 3 hours	
SD Card	Yes	Yes	No	Option		
Photozellen Input	Yes	Yes	Yes	Yes		
Manueller Input	Yes	Yes	Yes	Yes		
Audio Output	Yes	Yes	Yes	Yes		
Auxiliary Output	Intermediate Loops Red Lights Horn	Intermediate Loops Red Lights Horn	Red Lights Horn	RS485 or RS232		
RS232	Yes	Yes	Yes	No		
Ethernet TCP/IP	Yes	Yes	Yes	No		
Intermediate Loops	1 to 32	1 to 32	No	-		
Power	12 VDC	12 VDC	12 VDC	12 VDC	5,8 VDC / 110-230 V	9 V battery
USV	2 hours	2 hours	-	-		
Optionen			1 zusätzlicher Loop	GPS Synchronisation 1 zusätzlicher Loop SD Card reader		
Einsatztemperatur	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	-20°C to +55°C	> 0°C	-20°C to +70°C
Masse	160x100x52 mm	160x100x52 mm	160x100x52 mm	160x100x52 mm	450x340x105 mm	106x160x32 mm
Gewicht	590 gr	590 gr	515 gr	515 gr	2,5 Kg	240 gr
Packaged Weight	895 gr	895 gr	815 gr	815 gr	6,5 Kg with 40 transponders	240 gr
Garantie	3 Jahre	3 Jahre	3 Jahre	3 Jahre	3 Jahre	3 Jahre
Preise	7.580,- €	3.950,- €	1.990,- €	985,- €	490,- €	550,- €